

Fire Evacuation Key

Existing wall to achieve min 30 minute fire rating (suitability of wall to be confirmed on site by Pure Gym Main Contractor		Fire Escape Route
 Existing wall to achieve min 60 minute fire rating (suitability of wall to be confirmed on site by Pure Gym Main Contractor	* * 1050 min	Minimum Clear Widths
 New wall to achieve min of 30min fire rating	0	Exit No.
 New wall to achieve min of 60min fire rating		Shared Escape Route
Protected areas: walls, floors, ceilings and doors to achieve 30minute fire resistant construction.	FDXX	Fire Door Rating
Protected areas: walls, floors, ceilings and doors to achieve 60 minute fire resistant construction.		

Escape Route Widths: In line with Sections 3.21 & 3.22 of 'Approved Document Part B, Volume 2 - buildings other than dwellinghouses' - the adjacent calculations provide justification for the clear opening widths for escape from each floor level/ room in accordance with Table 4 & Appendix C. Ground Floor

<u>Ground Floor</u> Final Exit 1 limited by Storey Exit A Clear Opening Width = 1060mm (allows 222 persons to escape) Final Exit 2 Clear Opening Width = 1690mm (allows 348 persons to escape,largest opening to be discounted) Total Aggregate Width for Floor (Less Largest Opening Width of 1690mm from FINAL EXIT 2) = 1060mm

Total Ground Floor = 222 persons to escape

Based on NIA of 9947sqft, the Puregym Peak Occupancy Target = 171 Persons Calculated using Puregym Fire Safety Occupancy Levels Forecast Tool.

The design occupancy of the unit as calculated would allow a max. No. of 222 persons to escape, which is larger than the total estimated occupancy capacity of 171 persons and is therefore thought to meet with the 'Approved Document Part B'

Fire Alarm Fire Alarm designed and installed to BS 5839. Smoke & heat detection / emergency lighting by specialist. Please refer to M&E engineer's drawings / specifications.

Escape Lighting Emergency escape lighted designed and installed in accordance with BS 5266: Part 1. Please refer to M&E Engineer's drawings for final layout and specification. Escape Signage and emergency lighting is CDP under the M&E specification. Details of contractors proposals to be provided to Building Control Approved Inspector and Fire Officer within the Contractors Proposals Package, Clause 1.4

NOTE:

- Proposals must comply with all acoustic, fire & building regulation requirements
- No dimensions are to be scaled from this drawing. The contractor is responsible for checking all dimensions on site

